

Ms 207SR-102, Table AT10. Paleomagnetic analysis, Hole 1261A.

Core, section, interval (cm)	Depth (mcd)	Demagnetization (mT/°C)	Declination (°)	Inclination (°)	ChRM intensity (mA/m)	Error	Polarity assignments of Yusuke	Comments				
207-1261A-208-5, 132	369.42	NRM 0	328.8	15.4	1.33E-02	0.39	N?	Noisy, seems N-type				
		AF 50	352.9	34.4	1.27E-02	0.03						
		TT 150	337.2	20.4	8.75E-03	0.07						
		TT 150	336.2	19.7	7.39E-03	0.05						
		TT 200	0.1	3.8	5.73E-03	0.24						
		TT 200	1.6	12.1	5.81E-03	0.02						
		TT 240	326.2	8.5	5.03E-03	0.17						
		TT 240	329.5	-3.1	4.69E-03	0.22						
		TT 270	326.0	-14.5	4.14E-03	0.1						
		TT 270	328.3	-13.2	4.07E-03	0.12						
		TT 300	320.5	-14.9	2.15E-03	0.37						
		TT 300	325.8	-15	2.01E-03	0.31						
		TT 330	333.9	1.4	3.24E-03	0.31						
		TT 330	333.9	-1.9	3.74E-03	0.3						
		TT 360	314.9	-41.4	2.30E-03	0.84						
		TT 360	323.6	-53.6	3.02E-03	0.8						
20R-7, 43	371.43	NRM 0	60.1	2.9	1.09E-02	0.03	NP	N-type				
		AF 50	60.8	-0.3	9.27E-03	0.04						
		TT 150	65.0	-13.5	5.53E-03	0.1						
		TT 150	64.0	-15.5	5.27E-03	0.13						
		TT 200	65.1	-21.1	4.69E-03	0.07						
		TT 200	66.4	-19.5	4.78E-03	0.03						
		TT 250	64.3	-25.9	4.21E-03	0.07						
		TT 250	64.5	-15.9	3.74E-03	0.12						
		TT 300	69.3	-12.9	3.08E-03	0.11						
		TT 300	72.7	-27.5	3.18E-03	0.23						
		21R-1, 17	371.97	NRM 0	338.7	46.0			1.35E-02	0.03	RP	Hook-type
				AF 50	306.4	20.0			1.24E-02	0.03		
				TT 150	295.1	5.3			1.67E-02	0.03		
				TT 200	295.2	5.4			1.77E-02	0.04		
				TT 250	294.9	10.5			1.66E-02	0.02		
				TT 300	296.4	0.1			1.51E-02	0.03		
TT 350	293.6			4.6	1.23E-02	0.03						
TT 400	292.3			-6.9	1.17E-02	0.06						
21R-1, 68	372.48			NRM 0	333.4	15.3	3.30E-02	0.06	N	Nice N		
				AF 50	328.2	8.6	2.76E-02	0.04				
				TT 150	325.7	4.2	1.84E-02	0.06				
				TT 200	325.0	2.6	1.65E-02	0.04				
				TT 250	321.0	-0.4	1.45E-02	0.06				
				TT 300	323.5	-5.1	1.20E-02	0.07				
				TT 350	325.1	3.9	9.30E-03	0.06				
				TT 400	317.5	-0.8	8.19E-03	0.19				
		21R-3, 14	374.72	NRM 0	95.7	71.6	1.15E-02	0.08			RP	Hook-type
				AF 50	133.1	53.8	9.87E-03	0.08				
				TT 150	143.8	15.7	1.37E-02	0.09				
				TT 200	142.3	14.2	1.47E-02	0.06				
				TT 250	146.2	17.5	1.38E-02	0.04				
				TT 300	141.9	14.7	1.02E-02	0.07				
				TT 350	143.4	14.9	8.29E-03	0.13				
				TT 400	161.6	8.5	8.05E-03	0.15				
21R-3, 30	374.88			NRM 0	18.8	25.1	3.66E-02	0	N	Nice N		
				AF 50	17.9	23.2	3.10E-02	0.02				
				TT 150	15.4	20.3	2.77E-02	0.05				
				TT 200	11.0	14.0	1.99E-02	0.05				
				TT 240	12.3	15.4	1.82E-02	0.07				
				TT 270	8.0	13.0	1.55E-02	0.02				
				TT 300	6.3	12.9	1.27E-02	0.04				
				TT 330	6.8	13.5	1.06E-02	0.08				
		TT 360	201.2	81.2	1.03E-02	0.36						
		TT 400	1.3	6.8	7.98E-03	0.03						
		23R-1, 27	391.37	NRM 0	48.5	25.3	5.98E-03	0.12			R?	Hook-type
				NRM 0	67.3	29.6	5.24E-03	0.12				
				AF 50	60.8	26.2	7.49E-03	0.09				
				AF 50	62.0	28.0	8.22E-03	0.1				
				TT 150	82.5	-20.5	4.21E-03	0.1				
				TT 150	78.4	-26.9	4.10E-03	0.11				
TT 200	73.2			-16.2	3.03E-03	0.03						
TT 200	72.9			-24.3	3.16E-03	0.06						
TT 240	74.4			-2.2	3.77E-03	0.29						
TT 240	74.0			-3.6	3.61E-03	0.29						
TT 270	88.6			-21.9	2.57E-03	0.09						
TT 270	93.5			-19.9	2.37E-03	0.1						
TT 300	111.0			-13.1	2.17E-03	0.13						
TT 300	104.1			-8.4	1.99E-03	0.28						
TT 330	148.3			1.1	1.53E-03	0.51						
TT 330	145.5			6.6	1.58E-03	0.4						
TT 360	187.8	-72.7	4.94E-03	0.98								
TT 360	170.5	-30.7	1.87E-03	0.56								
23R-3, 37	394.47	NRM 0	336.0	73.9	8.24E-03	0.04	R	Hook-type				
		AF 50	275.5	50.7	6.56E-03	0.07						
		TT 150	255.1	22.2	7.52E-03	0.08						
		TT 200	254.1	16.3	8.00E-03	0.06						
		TT 250	253.7	15.3	8.06E-03	0.08						
		TT 300	249.5	7.0	6.84E-03	0.06						
		TT 350	246.7	5.5	5.61E-03	0.1						
		TT 400	243.5	-0.3	3.69E-03	0.17						
		TT 400	237.4	1.5	3.69E-03	0.24						
		23R-5, 38	397.48	NRM 0	45.2	25.2			1.13E-02	0.03	R	Hook-type (nice)
				AF 50	40.5	11.8			1.12E-02	0.02		
				TT 150	55.2	1.6			1.38E-02	0.06		
				TT 200	54.0	2.0			1.42E-02	0.03		
				TT 250	54.2	1.2			1.27E-02	0.04		
				TT 300	57.5	2.1			1.07E-02	0.02		
				TT 350	58.6	-1.5			8.87E-03	0.05		
TT 400	54.7			-4.4	8.18E-03	0.07						
23R-7, 35	400.45			NRM 0	2.9	36.8	4.15E-02	0	R	Hook-type		
				AF 50	2.8	22.2	3.16E-02	0.03				
				TT 150	2.5	14.6	3.08E-02	0.03				
				TT 200	1.6	7.7	3.27E-02	0.04				
				TT 240	1.8	7.9	3.19E-02	0.03				
				TT 270	0.5	7.8	3.20E-02	0.03				
				TT 300	358.9	6.1	3.03E-02	0.04				
				TT 330	359.4	3.6	2.76E-02	0.04				
		TT 360	353.7	5.1	2.53E-02	0.11						
		TT 400	1.0	5.8	2.37E-02	0.04						
		24R-1, 24	400.94	NRM 0	277.4	31.9	2.07E-02	0.04			R	Hook-type
				AF 50	261.1	14.5	2.36E-02	0.03				
				TT 150	254.1	6.8	2.88E-02	0.04				
				TT 200	253.6	2.5	2.99E-02	0.04				
				TT 250	253.8	6.5	2.84E-02	0.06				
				TT 300	250.6	5.1	2.56E-02	0.03				
TT 350	250.8			4.5	2.26E-02	0.03						
TT 400	256.7			0.8	1.95E-02	0.06						
24R-3, 31	403.71			NRM 0	321.7	14.8	3.36E-02	0.07	NP	N-type		
				AF 50	317.7	6.0	2.59E-02	0.02				
				TT 150	315.3	0.4	1.82E-02	0.03				
				TT 200	316.9	-2	1.59E-02	0.02				
				TT 250	311.7	-3.1	1.54E-02	0.04				
				TT 250	325.0	-9.6	1.45E-02	0.25				
				TT 300	313.9	-6.9	1.50E-02	0.04				
				TT 350	311.0	-11.8	1.61E-02	0.04				
		TT 400	314.7	-8.1	1.54E-02	0.07						
		24R-5, 32	406.52	NRM 0	162.0	7.3	5.23E-02	0.04			N	Nice N
				AF 50	165.9	0.1	4.80E-02	0.05				
				TT 150	170.7	0.0	4.36E-02	0.03				
				TT 200	170.5	-6.2	3.58E-02	0.06				
				TT 240	169.0	-4.9	3.42E-02	0.03				
				TT 270	170.7	-6.3	3.36E-02	0.06				
				TT 300	171.9	-8.7	2.98E-02	0.07				
TT 330	172.0			-12.2	2.75E-02	0.06						
TT 360	172.6			-10.3	2.46E-02	0.1						
TT 400	169.9			-5.8	2.37E-02	0.06						
25R-1, 51	410.81			NRM 0	145.2	18.5	3.82E-02	0.07	N	Nice N		
				AF 50	153.1	9.8	3.17E-02	0.05				
				TT 150	154.1	2.8	2.57E-02	0.04				
				TT 200	153.9	0.7	2.24E-02	0.04				
				TT 250	154.3	-0.6	2.08E-02	0.04				
				TT 300	156.9	-0.3	1.79E-02	0.04				
		TT 350	157.2	-3.7	1.57E-02	0.09						
		TT 400	163.0	-1.8	1.23E-02	0.05						
		25R-3, 49	413.63	NRM 0	311.8	11.9	5.04E-02	0.05			N	Nice N
				AF 50	308.6	6.6	3.99E-02	0.05				
				TT 150	306.3	1.1	3.08E-02	0.02				
				TT 200	306.0	-0.9	2.64E-02	0.02				
				TT 250	306.1	-2.7	2.30E-02	0.02				
				TT 300	307.8	0.6	1.96E-02	0.05				
				TT 350	308.7	-0.5	1.72E-02	0.06				
				TT 400	302.8	-3.3	1.45E-02	0.04				
25R-5, 38	416.52			NRM 0	286.6	17.3	4.31E-02	0.03	N	Nice N		
				AF 50	289.1	3.7	3.37E-02	0.08				
				TT 150	283.9	5.3	3.19E-02	0.03				
				TT 200	285.8	0.3	2.46E-02	0.02				
				TT 240	287.7	2.1	2.22E-02	0.08				
				TT 270	285.6	-1	2.13E-02	0.04				
				TT 300	287.2	-1.8	2.00E-02	0.02				
				TT 330	287.5	-3.9	1.81E-02	0.05				
		TT 360	286.7	-3.1	1.88E-02	0.1						
		TT 400	287.2	4.1	1.68E-02	0.04						
		26R-1, 23	420.13	NRM 0	348.9	45.8	1.64E-02	0.08			RP	Hook-type
				AF 50	172.0	50.9	7.22E-03	0.18				
				TT 150	101.0	21.0	6.43E-03	0.1				
				TT 150	94.4	17.2	6.23E-03	0.13				
				TT 200	107.9	3.4	8.91E-03	0.05				
				TT 250	105.7	1.1	9.91E-03	0.08				
TT 300	115.1			-0.2	7.98E-03	0.11						
TT 350	130.6			-16.9	7.79E-03	0.12						
TT 400	137.0			-20.3	5.54E-03	0.13						
TT 400	138.9			-25	5.41E-03	0.22						
26R-3, 7	422.57			NRM 0	294.7	32.3	1.56E-02	0.11	R	Hook-type		
				AF 50	288.9	11.1	1.82E-02	0.12				
				TT 150	286.0	-1.5	2.00E-02	0.09				
				TT 200	286.1	2.2	2.18E-02	0.06				