

Core, section, interval (cm)	Depth (mcd)	Demagnetization	Declination (°)	Inclination (°)	ChRM intensity (mT/C)	Error	Polarity assignments of Yusaue	Comments	Core, section, interval (cm)	Depth (mcd)	Demagnetization	Declination (°)	Inclination (°)	ChRM intensity (mT/C)	Error	Polarity assignments of Yusaue	Comments	Core, section, interval (cm)	Depth (mcd)	Demagnetization	Declination (°)	Inclination (°)	ChRM intensity (mT/C)	Error	Polarity assignments of Yusaue	Comments	
207-1260																			238.5, 35	334.85							
18.1, 48	40.68																										
NM0	284.1	8.1	5.43E-03	0.08																							
AF 50	284.1	8.8	4.92E-03	0.23																							
AF 50	277.0	7.5	5.51E-03	0.11																							
AF 50	276.6	1.2	4.53E-03	0.10																							
TT250	276.2	8.7	3.63E-03	0.04																							
TT250	275.2	16.2	3.82E-03	0.20																							
TT250	277.9	28.8	2.71E-03	0.37																							
TT250	276.3	28.5	3.18E-03	0.28																							
TT240	286.4	30.0	2.73E-03	0.21																							
TT240	285.3	23.9	3.23E-03	0.12																							
TT270	278.4	19.3	3.69E-03	0.27																							
TT270	280.6	17.4	3.26E-03	0.10																							
TT270	283.9	17.2	2.68E-03	0.16																							
TT300	284.9	11.1	3.31E-03	0.22																							
18.3, 66	43.86																										
NM0	304.8	4.7	1.06E-02	0.04																							
AF 50	300.0	-0.3	8.44E-03	0.04																							
AF 50	301.2	-0.3	8.27E-03	0.04																							
AF 50	295.4	16.1	1.25E-02	0.11																							
TT200	284.6	1.3	3.13E-03	0.21																							
TT260	4.1	3.14E-03																									
TT240	269.1	-10.7	3.46E-03	0.10																							
TT240	268.5	-16.4	2.39E-03	0.08																							
TT270	272.2	16.6	2.19E-03	0.08																							
TT270	273.4	-1.6	2.86E-03	0.09																							
TT300	284.5	28	2.73E-03	0.28																							
TT300	263.5	-23.1	3.24E-03	0.35																							
18.5, 4	46.24																										
NM0	71.7	35.1	9.71E-03	0.14																							
NM0	71.6	39.3	8.91E-03	0.05																							
AF 50	98.4	8.1	8.88E-03	0.04																							
AF 50	94.0	8.4	9.09E-03	0.04																							
TT150	112.1	-34.9	6.61E-03	0.04																							
TT150	-07.3	7.13E-03																									
TT200	113.4	-2.2	1.18E-02	0.03																							
TT270	116.2	-1	1.13E-02	0.01																							
TT300	120.4	-5.6	1.02E-02	0.04																							
TT300	112.4	8.0	9.86E-03	0.10																							
TT350	112.8	2.5	9.53E-03	0.14																							
18.5, 4	53.34																										
NM0	311.3	43.7	1.18E-02	0.04																							
NM0	316.0	18.0	1.36E-02	0.03																							
TT150	388.5	1.1	1.33E-02	0.02																							
TT200	360.0	8.7	1.61E-02	0.05																							
TT240	259.8	4.2	1.62E-02	0.02																							
TT270	258.1	6.3	1.59E-02	0.01																							
TT300	256.6	0.7	1.56E-02	0.06																							
TT350	256.0	8.7	1.30E-02	0.08																							
28.3, 131	53.34																										
NM0	148.6	17.0	2.13E-02	0.10																							
AF 50	153.4	7.7	2.51E-02	0.10																							
AF 50	152.9	7.6	2.48E-02	0.10																							
TT150	151.1	10.2	2.74E-02	0.11																							
TT200	151.7	4.2	2.57E-02	0.11																							
TT250	150.0	2.1	2.46E-02	0.09																							
TT270	153.3	4.6	2.38E-02	0.10																							
TT270	151.8	2.6	2.34E-02	0.09																							
TT350	150.3	4.0	2.09E-02	0.13																							
28.5, 33	55.36																										
NM0	130.3	12.0	2.71E-02	0.02																							
AF 50	136.3	-0.3	3.33E-02	0.01																							
TT150	140.9	-5.5	3.43E-02	0.03																							
TT200	138.6	-5.6	3.31E-02	0.05																							
TT240	141.0	-5.6	3.07E-02	0.05																							
TT270	140.4	-5.4	3.06E-02	0.04																							
TT300	139.5	-6.1	2.96E-02	0.03																							
TT350	141.5	-5.9	2.33E-02	0.05																							
38.1, 141	59.31																										
NM0	358.3	19.3	1.33E-02	0.02																							
AF 50	357.7	9.1	1.46E-02	0.07																							
TT150	359.5	9.9	1.41E-02	0.10																							
TT200	358.8	5.0	1.45E-02	0.07																							
TT240	8.2	8.4	1.37E-02	0.58																							
TT270	1.9	3.1	1.29E-02	0.01																							
TT300	2.2	1.7	1.24E-02	0.10																							
TT350	1.7	9.8	1.07E-02	0.11																							
38.3, 37	60.97																										
NM0	85.3	6.0	1.17E-02	0.08																							
AF 50	103.6	4.9	1.56E-02	0.19																							
TT150	112.5	6.3	1.66E-02	0.10																							
TT200	106.9	-1.8	1.58E-02	0.07																							
TT240	104.8	-1.6	1.51E-02	0.58																							
TT270	105.9	-0.1	1.38E-02	0.13																							
TT300	110.0	-7.1	1.26E-02	0.09																							
TT350	103.3	-4.6																									