

Summary Thermal Conductivity Data

Leg	Site	Lat	Lon	k av	k(0)	slope	k mat	phi(0)	D
				W/(m K)	W/(m K)	W/(m ² K)	W/(m K)		m
102	418 A	25.036	-68.062	1.00	-	-	-	-	-
104	644 A	66.680	4.577	1.18	-	-	-	-	-
105	646 A	58.210	-48.370	-	-	-	1.07	0.43	46
107	650 A	39.360	13.901	-	-	-	1.06	0.65	25
107	651 A	40.150	12.757	-	0.93	4.1E-03	-	-	-
107	652 A	40.360	12.143	-	-	-	2.02	0.62	223
107	653 A	40.260	11.450	-	-	-	1.47	0.51	128
107	654 A	40.580	10.697	-	1.18	6.3E-04	-	-	-
107	655 A	40.180	12.465	-	-	-	1.20	0.40	6
108	661 B	9.447	-19.390	-	-	-	1.75	0.57	300
108	663 B	-1.200	-11.880	-	0.88	4.3E-03	-	-	-
108	667 B	4.569	-21.910	-	0.97	2.4E-03	-	-	-
110	671 B	15.530	-58.730	-	-	-	1.41	0.41	88
110	672 A	15.540	-58.640	-	1.19	6.3E-04	-	-	-
110	673 A	15.530	-58.730	-	-	-	1.24	0.30	25
110	674 A	15.540	-58.850	-	1.16	5.7E-04	-	-	-
110	676 A	15.530	-58.700	-	-	-	1.21	0.36	18
111	677 A	1.204	-83.739	-	0.85	1.1E-03	-	-	-
112	680 B	-11.100	-78.080	0.92	-	-	-	-	-
112	681 B	-11.000	-77.960	0.00	0.83	2.9E-03	-	-	-
112	683 A	-9.030	-80.410	0.87	-	-	-	-	-
112	684 A	-8.990	-79.910	-	-	-	0.90	0.58	2
112	686 A	-13.500	-76.890	-	1.03	-1.2E-03	-	-	-
112	687 A	-12.900	-76.990	-	1.14	-1.7E-03	-	-	-
112	688 A	-11.500	-78.940	0.98	-	-	-	-	-
113	690 B	-65.200	1.205	-	0.88	5.1E-03	-	-	-
113	695 A	-62.400	-43.450	-	0.95	2.0E-03	-	-	-
113	696 B	-61.800	-42.930	-	1.11	2.1E-03	-	-	-
115	709 A	-3.920	60.552	-	-	-	1.35	0.22	46
116	717 C	-0.930	81.390	-	-	-	1.53	0.44	310
116	718 C	-1.020	81.401	-	-	-	2.26	0.53	327
116	719 A	-0.960	81.400	-	1.27	4.4E-04	-	-	-
117	728 B	17.680	57.826	0.00	1.37	-1.0E-03	-	-	-
117	731 A	16.470	59.703	1.19	-	-	-	-	-
119	736 A	-49.400	71.662	0.63	-	-	-	-	-
119	737 A	-50.200	73.032	0.86	-	-	-	-	-
119	744 A	-61.600	80.595	-	-	-	1.42	0.85	59
119	745 B	-59.600	85.854	-	-	-	0.93	0.61	40
120	747 A	-54.800	76.794	-	-	-	1.40	0.68	23
120	748 B	-58.400	78.998	-	-	-	1.53	0.52	70
121	752 A	-30.900	93.578	-	-	-	1.55	0.31	63
122	760 A	-16.900	115.540	-	-	-	2.11	0.51	133

Summary Thermal Conductivity Data

122	761 B	-16.700	115.540	-	-	-	1.45	0.36	32
122	762 B	-19.900	112.250	-	1.20	1.4E-03	-	-	-
122	763 A	-20.600	112.210	-	1.32	9.9E-04	-	-	-
125	780 D	19.540	146.650	-	1.30	9.5E-03	-	-	-
125	783 A	30.960	141.790	-	0.94	-8.8E-04	-	-	-
125	784 A	30.910	141.740	0.90	-	-	-	-	-
126	792 A	32.400	140.380	-	0.97	1.9E-04	-	-	-
127	794 A	40.190	138.230	-	0.92	-4.0E-04	-	-	-
127	795 A	43.990	138.970	-	0.81	2.2E-04	-	-	-
127	796 A	42.850	139.410	0.87	-	-	-	-	-
127	797 B	38.620	134.540	0.85	-	-	-	-	-
128	798 A	37.040	134.800	0.83	-	-	-	-	-
128	799 A	39.220	133.870	0.98	-	-	-	-	-
131	808 B	32.350	134.940	-	1.00	1.4E-03	-	-	-
134	827A	-15.300	166.350	-	0.96	6.0E-04	-	-	-
134	829 C	-15.300	166.350	-	0.97	3.8E-03	-	-	-
134	830 A	-16.000	166.780	-	0.96	6.5E-03	-	-	-
134	831 A	-16.000	166.670	1.00	-	-	-	-	-
134	832 A	-14.800	167.570	-	-	-	1.44	0.68	285
134	833 A	-14.900	167.880	-	-	-	1.07	0.44	26
135	834 A	-18.600	-177.900	-	1.12	-1.7E-03	-	-	-
135	835 A	-18.500	-177.300	-	0.90	4.2E-04	-	-	-
135	837 A	-20.200	-176.800	0.85	-	-	-	-	-
135	838 A	-20.800	-176.900	-	0.86	-1.1E-03	-	-	-
135	839 A	-20.700	-176.800	-	0.83	-3.7E-04	-	-	-
135	840 A	-22.200	-175.700	-	0.93	4.5E-04	-	-	-
135	841 A	-23.300	-175.300	-	0.88	1.0E-03	-	-	-
139	855 C	48.440	-128.600	-	-	-	1.23	0.22	25
139	856 A	48.440	-128.700	-	1.16	7.7E-03	-	-	-
139	856 B	48.440	-128.700	-	1.22	1.3E-02	-	-	-
139	857 A	48.440	-128.700	-	1.02	5.2E-03	-	-	-
139	857 C	48.440	-128.700	-	1.08	4.7E-03	-	-	-
139	858 A	48.460	-128.700	-	0.95	9.9E-03	-	-	-
139	858 B	48.460	-128.700	-	0.91	4.1E-02	-	-	-
139	858 C	48.460	-128.700	-	1.05	2.2E-02	-	-	-
141	859 A	-45.900	-75.850	-	1.12	1.5E-03	-	-	-
141	860 B	-45.900	-75.750	-	1.05	1.2E-03	-	-	-
141	861 C	-45.900	-75.690	-	1.08	5.4E-04	-	-	-
141	863 A	-46.200	-75.770	-	1.28	9.7E-04	-	-	-
145	881 C	47.100	161.490	1.00	-	-	-	-	-
146	888 B	48.170	-126.700	-	-	-	2.14	0.35	161
146	889 A	48.700	-126.900	1.40	-	-	-	-	-
146	890 B	48.660	-126.900	1.53	-	-	-	-	-
146	892 A	44.670	-125.100	-	1.13	2.1E-03	-	-	-

Summary Thermal Conductivity Data

149	897 C	40.840	-12.470	-	1.06	7.4E-04	-	-	-
149	898 A	40.650	-12.120	-	1.23	6.2E-04	-	-	-
149	900 A	46.680	-11.600	-	1.11	1.3E-03	-	-	-
150	902 C	38.930	-72.770	-	1.21	6.4E-04	-	-	-
150	903 A	38.940	-72.820	-	1.19	7.8E-04	-	-	-
151	907A	69.250	12.700	-	1.09	-2.4E-03	-	-	-
151	908 A	78.390	1.361	-	1.54	-1.6E-03	-	-	-
151	909 A	78.580	3.072	-	1.19	6.1E-04	-	-	-
151	910 C	80.260	6.590	-	1.39	1.0E-02	-	-	-
151	911 A	80.470	8.227	-	1.11	6.9E-04	-	-	-
151	912 A	79.960	5.456	1.34	-	-	-	-	-
152	918 A	63.090	-38.640	-	1.17	1.7E-03	-	-	-
154	926 C	3.719	-42.910	-	-	-	1.33	0.56	52
155	930 B	5.015	-47.596	-	0.94	1.4E-03	0.00	0.00	0
155	931 B	5.142	-46.633	-	-	-	1.25	0.59	93
155	932 A	5.211	-47.030	1.18	-	-	-	-	-
155	933 A	5.097	-46.812	1.07	-	-	-	-	-
155	934 A	5.484	-47.681	1.07	-	-	-	-	-
155	935 A	5.427	-47.565	-	-	-	1.33	0.63	90
155	936 A	5.632	-47.736	1.20	-	-	-	-	-
155	937 B	4.596	-47.207	1.07	-	-	-	-	-
155	938 A	4.658	-47.312	1.07	-	-	-	-	-
155	939 B	4.722	-47.503	1.07	-	-	-	-	-
155	940 A	5.143	-47.529	1.02	-	-	-	-	-
155	941 A	5.373	-48.029	1.02	-	-	-	-	-
155	942 A	5.743	-49.091	1.07	-	-	-	-	-
155	944 A	5.939	-47.758	1.02	-	-	-	-	-
155	946 A	6.950	-47.919	1.02	-	-	-	-	-
156	948 C	15.530	-58.730	-	-	-	1.57	0.47	712
156	949 B	15.540	-58.710	-	0.99	5.6E-04	-	-	-
157	954 A	28.440	-15.530	-	0.93	2.7E-03	-	-	-
157	955 A	27.330	-15.230	1.09	-	-	-	-	-
157	956 A	27.620	-16.160	1.09	-	-	-	-	-
159	959A	3.628	2.735	-	-	-	1.12	0.18	37
159	959B	3.628	2.736	-	-	-	1.12	0.18	37
160	963 B	37.032	13.182	-	-	-	1.52	0.34	153
160	964 B	36.260	17.750	1.14	-	-	-	-	-
160	966 A	33.797	32.702	-	1.04	5.1E-03	-	-	-
160	967 A	34.068	32.725	-	1.00	4.5E-03	-	-	-
160	968 A	34.332	32.751	-	1.18	1.1E-03	-	-	-
160	969 A	33.840	24.885	-	1.26	2.1E-03	-	-	-
160	970 A	33.737	24.802	-	1.35	-1.1E-03	-	-	-
160	971 A	33.703	24.714	-	1.09	1.7E-02	-	-	-
160	972 A	35.780	18.725	1.30	-	-	-	-	-

Summary Thermal Conductivity Data

160	973 A	35.780	18.948	1.30	-	-	-	-	-
161	974B	40.360	12.147	-	-	-	1.35	0.38	44
161	975C	38.905	4.517	-	-	-	1.50	0.18	87
161	976B	36.209	4.322	-	-	-	1.47	0.26	252
161	977A	36.042	-1.959	-	1.16	9.8E-04	-	-	-
161	979A	35.721	-3.210	1.01	-	-	0.00	0.00	0
162	981C	55.477	-14.651	-	1.12	4.1E-04	-	-	-
162	984B	61.425	-24.082	-	0.89	5.5E-04	-	-	-
162	986C	77.341	9.078	1.05	-	-	-	-	-
162	987B	70.497	-17.937	1.24	-	-	-	-	-
164	994C	31.786	-75.546	0.95	-	-	-	-	-
164	995AB	31.804	-75.522	0.98	-	-	-	-	-
164	997A	31.843	-75.469	0.99	-	-	-	-	-
166	1003AB	24.546	-79.261	-	1.02	2.0E-03	-	-	-
166	1004A	24.555	-79.249	1.09	-	-	-	-	-
166	1005AB	24.563	-79.236	1.08	-	-	-	-	-
166	1006A	24.400	-79.459	-	1.08	8.8E-04	-	-	-
166	1007B	24.504	-79.322	1.20	-	-	-	-	-
166	1008A	23.611	-79.084	-	1.00	3.4E-03	-	-	-
166	1009A	23.614	-79.050	-	1.04	7.1E-04	-	-	-
167	1010D	29.965	-118.101	0.94	-	-	-	-	-
167	1011C	31.280	-117.634	0.00	-	-	1.05	0.29	23
167	1012B	32.283	-118.384	0.89	-	-	-	-	-
167	1013C	32.801	-118.899	0.87	-	-	-	-	-
167	1014B	32.834	-119.981	0.82	-	-	-	-	-
167	1016A	34.540	-122.277	0.82	-	-	-	-	-
167	1017B	34.535	-121.107	0.92	-	-	-	-	-
167	1018A	36.988	-123.278	0.82	-	-	-	-	-
167	1019C	41.683	-124.933	0.97	-	-	-	-	-
167	1020B	41.001	-126.434	0.00	0.85	1.1E-03	-	-	-
167	1021B	39.087	-127.783	0.83	-	-	-	-	-
167	1022A	40.081	-125.343	0.93	-	-	-	-	-
168	1023 A	47.918	-128.798	-	-	-	1.17	0.36	25
168	1024 B	47.908	-128.754	-	1.11	2.9E-04	-	-	-
168	1025 B	47.894	-128.651	-	1.13	9.3E-04	-	-	-
168	1026 A	47.771	-127.765	-	-	-	1.45	0.76	10
168	1026 C	47.771	-127.765	1.38	-	-	-	-	-
168	1027 B	47.761	-127.740	-	0.72	1.7E-03	-	-	-
168	1028 A	47.863	-128.508	-	-	-	1.28	0.31	28
168	1029 A	47.842	-128.383	-	-	-	1.38	0.31	39
168	1031 A	47.894	-128.577	1.10	-	-	-	-	-
168	1032 A	47.788	-128.126	1.36	-	-	-	-	-
169	1035A	48.434	-128.682	-	0.99	4.3E-03	-	-	-
169	1035E	48.433	-128.681	-	0.89	1.2E-02	-	-	-

Summary Thermal Conductivity Data

169	1036C	48.457	-128.711	-	0.94	1.9E-02	-	-	-
169	1037B	40.955	-127.515	-	-	-	1.28	0.45	48
169	1038I	40.998	-127.493	-	0.94	8.3E-03	-	-	-
170	1039B	9.640	-86.200	0.00	0.79	-1.4E-04	-	-	-
170	1040BC	9.662	-86.179	0.91	-	-	-	-	-
170	1041AB	9.734	-86.116	0.82	-	-	-	-	-
171	1051B	30.053	-76.358	1.10	-	-	-	-	-
171	1053B	29.992	-76.524	-	1.10	1.4E-03	-	-	-
172	1062A	28.246	-74.407	-	0.91	1.3E-03	-	-	-
172	1063B	33.686	-57.615	-	-	-	1.04	0.27	99
174A	1073A	39.225	-72.276	-	1.02	3.8E-04	-	-	-
174B	1074A	22.781	-46.112	1.07	-	-	-	-	-
175	1076A	-5.069	11.102	0.79	-	-	-	-	-
175	1077A	-5.180	10.437	0.73	-	-	-	-	-
175	1078A	-11.920	13.400	0.95	-	-	-	-	-
175	1081A	-19.620	11.319	-	0.85	-6.1E-04	-	-	-
175	1082A	-21.094	11.082	-	0.79	-1.3E-03	-	-	-
175	1084A	-25.514	13.028	0.69	-	-	-	-	-
175	1085A	-29.374	13.990	0.98	-	-	-	-	-
175	1087A	-31.465	15.311	-	-	-	1.13	0.38	43
177	1088B	-41.137	13.563	-	-	-	1.15	0.52	19
177	1089A	-40.937	9.893	-	0.88	3.0E-04	-	-	-
177	1093A	-49.977	5.865	0.79	-	-	-	-	-
177	1094A	-53.180	5.130	-	0.63	4.1E-04	-	-	-
178	1096B	-67.567	-76.963	1.05	-	-	-	-	-
178	1098B	-64.528	-64.208	-	0.58	7.0E-03	-	-	-
178	1099A	-64.945	-64.315	0.70	-	-	-	-	-
178	1101A	-64.372	-70.262	-	-	-	1.07	0.48	30
180	1108B	-9.745	151.625	-	-	-	1.42	0.63	155
180	1109C	-9.507	151.573	0.92	-	-	-	-	-
180	1115B	-9.190	151.574	0.96	-	-	-	-	-