

Bit No.	Time/Date (TOD)	Core No.	Hours Since Last Core	Rotating Time (min)	Total Cores	Meters Cored	Meters Recovery	Percent Recovery	ROP (m/hr)	Bit Hours	Bit Total (hours)	Bit Total (meters)	Depth (mbsf)	Remarks
1	26-Oct	89R	n/a	70	1	3.0	2.05	68.3%	2.57	1.2	1.2	3.0	507.8	0.7m w/ncb
		90R	4.1	200	1	9.6	9.88	102.9%	2.88	3.3	4.5	12.6	517.4	55 rpm/22k
		91R	4.3	210	1	9.6	5.87	61.1%	2.74	3.5	8.0	22.2	527.0	liner jam
		92R	3.3	160	1	5.1	2.23	43.7%	1.91	2.7	10.7	27.3	532.1	liner jam
	27-Oct	93R	3.3	140	1	4.5	5.02	111.6%	1.93	2.3	13.0	31.8	536.6	60 rpm/22k
		94R	5.2	240	1	8.0	3.48	43.5%	2.00	4.0	17.0	39.8	544.6	liner jam
		95R	3.5	165	1	3.7	3.00	81.1%	1.35	2.8	19.8	43.5	548.3	20-30k
96R		9.3	370	1	8.0	2.79	34.9%	1.30	6.2	25.9	51.5	556.3	POOH	
2	28-Oct	97R	<b>13.3</b>	215	1	4.7	4.89	104.0%	1.31	3.6	29.5	56.2	561.0	bit break in
		98R	2.1	60	1	4.9	2.28	46.5%	4.90	1.0	30.5	61.1	565.9	liner jam
		99R	5.1	210	1	9.6	7.49	78.0%	2.74	3.5	34.0	70.7	575.5	w/o c/liner
		100R	4.2	210	1	9.6	3.00	31.3%	2.74	3.5	37.5	80.3	585.1	w/o c/liner
	29-Oct	101R	3.3	180	1	4.8	3.86	80.4%	1.60	3.0	40.5	85.1	589.9	w/o c/liner
		102R	2.5	115	1	4.9	3.53	72.0%	2.56	1.9	42.4	90.0	594.8	w/o c/liner
		103R	3.4	165	1	9.5	5.81	61.2%	3.45	2.8	45.2	99.5	604.3	w/o c/liner
		104R	2.3	100	1	4.5	2.53	56.2%	2.70	1.7	46.8	104.0	608.8	w/o c/liner
		105R	3.8	180	1	5.1	4.70	92.2%	1.70	3.0	49.8	109.1	613.9	w/o c/liner
		106R	3.3	160	1	5.6	4.91	87.7%	2.10	2.7	52.5	114.7	619.5	w/o c/liner
		107R	2.1	95	1	4.0	3.01	75.3%	2.53	1.6	54.1	118.7	623.5	w/o c/liner
		108R	3.3	140	1	5.2	5.05	97.1%	2.23	2.3	56.4	123.9	628.7	w/o c/liner
	30-Oct	109R	2.8	110	1	4.4	4.55	103.4%	2.40	1.8	58.3	128.3	633.1	w/o c/liner
		110R	2.8	130	1	4.9	5.18	105.7%	2.26	2.2	60.4	133.2	638.0	w/o c/liner
111R		2.6	90	1	4.7	3.26	69.4%	3.13	1.5	61.9	137.9	642.7	POOH	
3		112R	<b>16.7</b>	140	1	5.0	4.48	89.6%	2.14	2.3	64.3	142.9	647.7	bit break in
	31-Oct	113R	3.3	130	1	4.7	2.76	58.7%	2.17	2.2	66.4	147.6	652.4	w/o c/liner
		114R	5.4	280	1	9.6	7.92	82.5%	2.06	4.7	71.1	157.2	662.0	w/o c/liner
		115R	5.1	265	1	9.6	9.42	98.1%	2.17	4.4	75.5	166.8	671.6	w/o c/liner
		116R	4.5	225	1	9.6	7.96	82.9%	2.56	3.8	79.3	176.4	681.2	w/o c/liner
		117R	5.5	275	1	9.6	7.13	74.3%	2.09	4.6	83.8	186.0	690.8	w/o c/liner
	01-Nov	118R	5.2	275	1	9.6	9.50	99.0%	2.09	4.6	88.4	195.6	700.4	w/o c/liner
		119R	3.2	135	1	9.6	5.88	61.3%	4.27	2.3	90.7	205.2	710.0	w/o c/liner
		120R	4.1	215	1	9.7	9.27	95.6%	2.71	3.6	94.3	214.9	719.7	w/o c/liner
		121R	5.0	245	1	9.7	10.04	103.5%	2.38	4.1	98.3	224.6	729.4	w/o c/liner
		122R	4.0	190	1	9.6	9.28	96.7%	3.03	3.2	101.5	234.2	739.0	w/o c/liner
		123R	3.8	195	1	9.7	9.46	97.5%	2.98	3.3	104.8	243.9	748.7	w/o c/liner
	02-Nov	124R	2.1	55	1	3.4	3.33	97.9%	3.71	0.9	105.7	247.3	752.1	POOH

Bit No.	Time/Date (TOD)	Core No.	Hours Since Last Core	Rotating Time (min)	Total Cores	Meters Cored	Meters Recovery	Percent Recovery	ROP (m/hr)	Bit Hours	Bit Total (hours)	Bit Total (meters)	Depth (mbsf)	Remarks	
4		125R	<b>15.0</b>	100	1	3.2	0.57	17.8%	1.92	1.7	107.3	250.5	755.3	<b>drift 4.50°</b>	
		126R	3.4	140	1	9.6	7.90	82.3%	4.11	2.3	109.7	260.1	764.9	w/o c/liner	
		127R	3.1	130	1	9.6	6.38	66.5%	4.43	2.2	111.8	269.7	774.5	w/o c/liner	
	03-Nov		128R	3.6	165	1	9.7	6.16	63.5%	3.53	2.8	114.6	279.4	784.2	w/o c/liner
			129R	4.4	200	1	9.7	3.90	40.2%	2.91	3.3	117.9	289.1	793.9	w/o c/liner
			130R	4.4	230	1	9.6	4.30	44.8%	2.50	3.8	121.8	298.7	803.5	w/o c/liner
			131R	2.8	120	1	9.7	4.83	49.8%	4.85	2.0	123.8	308.4	813.2	w/o c/liner
			132R	4.2	200	1	9.7	9.46	97.5%	2.91	3.3	127.1	318.1	822.9	w/o c/liner
			133R	4.1	210	1	9.7	9.34	96.3%	2.77	3.5	130.6	327.8	832.6	w/o c/liner
	04-Nov		134R	4.6	220	1	9.6	9.60	100.0%	2.62	3.7	134.3	337.4	842.2	w/o c/liner
			135R	3.0	140	1	4.7	4.57	97.2%	2.01	2.3	136.6	342.1	846.9	w/o c/liner
			136R	2.4	100	1	4.9	4.69	95.7%	2.94	1.7	138.3	347.0	851.8	w/o c/liner
			137R	4.5	225	1	9.6	9.10	94.8%	2.56	3.8	142.0	356.6	861.4	w/o c/liner
			138R	4.7	230	1	9.7	8.78	90.5%	2.53	3.8	145.8	366.3	871.1	w/o c/liner
			139R	4.1	205	1	9.2	8.79	95.5%	2.69	3.4	149.3	375.5	880.3	w/o c/liner
05-Nov	140R	4.1	190	1	9.0	7.78	86.4%	2.84	3.2	152.4	384.5	889.3	<b>POOH</b>		
5	06-Nov	141R	<b>42.0</b>	105	1	3.6	2.54	70.6%	2.06	1.8	154.2	388.1	892.9	<b>bit break in</b>	
	07-Nov	142R	4.9	240	1	9.7	8.97	92.5%	2.43	4.0	158.2	397.8	902.6	TQ/30 bbls	
		143R	4.4	225	1	9.7	8.86	91.3%	2.59	3.8	161.9	407.5	912.3	TQ/30 bbls	
		144R	4.7	230	1	9.6	8.81	91.8%	2.50	3.8	165.8	417.1	921.9	TQ/30 bbls	
		145R	4.3	220	1	9.6	8.10	84.4%	2.62	3.7	169.4	426.7	931.5	TQ/30 bbls	
		146R	5.0	255	1	9.7	8.48	87.4%	2.28	4.3	173.7	436.4	941.2	30 bbls	
	08-Nov	147R	5.6	300	1	9.7	9.08	93.6%	1.94	5.0	170.75	426.8	931.6	30 bbls	
		148R	6.3	335	1	9.6	9.18	95.6%	1.72	5.6	176.33	436.4	941.2	30 bbls	
		149R	6.5	345	1	9.6	9.90	103.1%	1.67	5.8	5.75	9.6	9.6	20 bbls	
	09-Nov	150R	5.7	300	1	9.7	9.56	98.6%	1.94	5.0	10.75	19.3	19.3	30 bbls	
151R		5.3	285	1	7.7	7.80	101.3%	1.62	4.8	15.50	27.0	27.0	<b>TQ +40</b>		
6		152R	<b>15.6</b>	250	1	8.2	7.96	97.1%	1.97	4.2	19.67	35.2	35.2	<b>bit break in</b>	
		153R	5.3	270	1	9.6	8.65	90.1%	2.13	4.5	24.17	44.8	44.8	20 bbls	
	10-Nov	154R	5.4	275	1	9.7	8.34	86.0%	2.12	4.6	28.75	54.5	54.5	20 bbls	
		155R	5.8	300	1	9.7	9.34	96.3%	1.94	5.0	33.75	64.2	64.2	20 bbls	
		156R	5.1	265	1	9.6	9.86	102.7%	2.17	4.4	38.17	73.8	73.8	30 bbls	
		157R	4.2	210	1	9.7	8.33	85.9%	2.77	3.5	41.67	83.5	83.5	20 bbls	
		158R	3.8	215	1	9.7	9.54	98.4%	2.71	3.6	45.25	93.2	93.2	20 bbls	
	11-Nov	159R	3.8	180	1	9.7	8.83	91.0%	3.23	3.0	48.25	102.9	102.9	20 bbls	
		160R	4.5	210	1	9.6	9.33	97.2%	2.74	3.5	51.75	112.5	112.5	20 bbls	
		161R	4.2	200	1	9.6	9.77	101.8%	2.88	3.3	55.08	122.1	122.1	20 bbls	
162R		4.2	205	1	9.6	9.59	99.9%	2.81	3.4	58.50	131.7	131.7	20 bbls		
163R		4.1	175	1	7.2	6.81	94.6%	2.47	2.9	61.42	138.9	138.9	<b>TQ +40</b>		

Bit No.	Time/Date (TOD)	Core No.	Hours Since Last Core	Rotating Time (min)	Total Cores	Meters Cored	Meters Recovery	Percent Recovery	ROP (m/hr)	Bit Hours	Bit Total (hours)	Bit Total (meters)	Depth (mbsf)	Remarks
7	12-Nov	164R	<b>12.9</b>	115	1	5.9	4.61	78.1%	3.08	1.9	63.33	144.8	144.8	<b>10K/50 rpm</b>
		165R	4.0	190	1	5.6	7.00	125.0%	1.77	3.2	66.50	150.4	150.4	20 bbbs
		166R	4.2	215	1	9.6	8.65	90.1%	2.68	3.6	70.08	160.0	160.0	20 bbbs
		167R	4.9	250	1	9.6	9.05	94.3%	2.30	4.2	74.25	169.6	169.6	20 bbbs
	13-Nov	168R	4.1	200	1	9.6	9.21	95.9%	2.88	3.3	77.58	179.2	179.2	20 bbbs
		169R	5.1	225	1	9.6	8.39	87.4%	2.56	3.8	81.33	188.8	188.8	20 bbbs
		170R	3.8	190	1	9.7	9.86	101.6%	3.06	3.2	84.50	198.5	198.5	20 bbbs
		171R	4.7	235	1	9.7	9.66	99.6%	2.48	3.9	88.42	208.2	208.2	20 bbbs
		172R	3.8	180	1	9.7	9.14	94.2%	3.23	3.0	91.42	217.9	217.9	20 bbbs
	14-Nov	173R	2.9	135	1	9.7	8.54	88.0%	4.31	2.3	93.67	227.6	227.6	20 bbbs
174R		2.0	60	1	3.0	2.70	90.0%	3.00	1.0	94.67	230.6	230.6	<b>TQ +100</b>	
8		175R	<b>-8745.3</b>	125	1	5.6	5.52	98.6%	2.69	2.1	96.75	236.2	236.2	<b>10K/50 rpm</b>
		176R	2.3	90	1	5.0	4.00	80.0%	3.33	1.5	98.25	241.2	241.2	20 bbbs
		177R	3.1	140	1	9.6	9.23	96.1%	4.11	2.3	100.58	250.8	250.8	20 bbbs
		178R	3.4	160	1	9.6	9.48	98.8%	3.60	2.7	103.25	260.4	260.4	20 bbbs
	15-Nov	179R	3.4	160	1	9.6	9.92	103.3%	3.60	2.7	105.92	270.0	270.0	20 bbbs
		180R	3.3	135	1	9.7	7.74	79.8%	4.31	2.3	108.17	279.7	279.7	20 bbbs
		181R	2.4	95	1	9.7	4.89	50.4%	6.13	1.6	109.75	289.4	289.4	30 bbbs
		182R	2.8	120	1	9.7	4.44	45.8%	4.85	2.0	111.75	299.1	299.1	30 bbbs
		183R	3.4	160	1	9.6	7.34	76.5%	3.60	2.7	114.42	308.7	308.7	30 bbbs
		184R	3.8	170	1	9.6	7.67	79.9%	3.39	2.8	117.25	318.3	318.3	30 bbbs
		185R	3.9	185	1	9.6	8.61	89.7%	3.11	3.1	120.33	327.9	327.9	50 bbbs
	16-Nov	186R	3.3	155	1	8.8	8.09	91.9%	3.41	2.6	122.92	336.7	336.7	50 bbbs
		187R	5.2	165	1	9.7	7.25	74.7%	3.53	2.8	125.67	346.4	346.4	30 bbbs
		188R	4.1	185	1	9.6	9.05	94.3%	3.11	3.1	128.75	356.0	356.0	20 bbbs
		189R	5.2	270	1	9.6	9.22	96.0%	2.13	4.5	133.25	365.6	365.6	20 bbbs
		190R	5.0	255	1	9.6	8.22	85.6%	2.26	4.3	137.50	375.2	375.2	20 bbbs
	17-Nov	191R	5.2	260	1	9.6	9.22	96.0%	2.22	4.3	141.83	384.8	384.8	20 bbbs
		192R	4.9	250	1	9.7	9.52	98.1%	2.33	4.2	146.00	394.5	394.5	20 bbbs
		193R	3.3	150	1	5.6	1.39	24.8%	2.24	2.5	148.50	400.1	400.1	<b>TQ +/-50</b>
9	18-Nov	194R	<b>18.2</b>	70	1	3.5	3.48	99.4%	3.00	1.2	149.67	403.6	403.6	<b>10K/50 rpm</b>
		195R	4.3	180	1	9.6	9.13	95.1%	3.20	3.0	152.67	413.2	413.2	20 bbbs
		196R	4.1	180	1	9.6	8.39	87.4%	3.20	3.0	155.67	422.8	422.8	20 bbbs
		197R	3.1	95	1	3.1	4.44	143.2%	1.96	1.6	157.25	425.9	425.9	<b>WOW</b>

Bit No.	Time/Date (TOD)	Core No.	Hours Since Last Core	Rotating Time (min)	Total Cores	Meters Cored	Meters Recovery	Percent Recovery	ROP (m/hr)	Bit Hours	Bit Total (hours)	Bit Total (meters)	Depth (mbsf)	Remarks
10	20-Nov	198R	<u>37.7</u>	90	1	6.0	5.47	91.2%	4.00	1.5	158.75	431.9	431.9	<b>10K/50 rpm</b>
		199R	2.5	110	1	9.6	8.50	88.5%	5.24	1.8	160.58	441.5	441.5	20 bbls
		200R	2.9	120	1	9.6	8.98	93.5%	4.80	2.0	162.58	451.1	451.1	20 bbls
		201R	3.3	155	1	9.6	9.00	93.8%	3.72	2.6	165.17	460.7	460.7	20 bbls
		202R	3.8	175	1	9.6	9.75	101.6%	3.29	2.9	168.08	470.3	470.3	30 bbls
	21-Nov	203R	3.5	165	1	9.7	8.50	87.6%	3.53	2.8	170.83	480.0	480.0	30 bbls
		204R	3.7	165	1	9.7	8.99	92.7%	3.53	2.8	173.58	489.7	489.7	30 bbls
		205R	3.8	180	1	9.7	10.32	106.4%	3.23	3.0	176.58	499.4	499.4	30 bbls
		206R	3.7	160	1	9.6	8.07	84.1%	3.60	2.7	179.25	509.0	509.0	30 bbls
		207R	3.2	140	1	9.6	8.51	88.6%	4.11	2.3	181.58	518.6	518.6	30 bbls
		208R	4.6	185	1	9.6	9.57	99.7%	3.11	3.1	184.67	528.2	528.2	<b>drift 4.80°</b>
		209R	4.2	200	1	9.6	9.77	101.8%	2.88	3.3	188.00	537.8	537.8	30 bbls
	210R	4.1	190	1	9.7	8.93	92.1%	3.06	3.2	191.17	547.5	547.5	<b>DP failure</b>	

APPENDIX III - Coring Data  
Part D